

Zip Tex: Real Life Expectations

Insect and Shade

- Don't operate in windy conditions.
- Retract if winds exceed 40 mph winds.
- Clean fabric once a year, with soap and water.
- Fabric should not be overly tight, loose fitment is best suited for proper operation
- Spray silicone in tracks once a year.
- Don't operate in temps below freezing.
- Let dry after a rain, before running up.



Vinyl with Windows

- Rolling clear Vinyl will not look like glass, expect imperfections, such as waves, bumps, light scuffs and dimples.
- Don't operate in windy conditions.
- Retract if winds exceed 40 mph winds.
- Clean fabric once a year, with soap and water only, chemicals will degrade the vinyl.
- Spray silicone in tracks once a year.
- Apply a coat of IMAR wax quarterly to prevent sticking and causing operation failure.
- Don't operate in temps below 50°.
- After heavy moisture days, clear vinyl will fog. Leave down during daylight to allow drying to take place.



Remember, we have wind tested this product for general use, ***its not wind rated***. If any damage occurs due to wind, it will be considered neglect and will not be covered under standard warranty!

Alutech United, Inc. Shutters Solution - Any shape, Any size, Any time

117 Dixon Street, Selbyville, DE 19975 Phone: 302-436-6005, Fax: 302-436-5100, Toll free: 1-800-233-1144
1537 Northgate Blvd., Sarasota, FL 34234 - Phone: 941-355-0970, Fax: 941-355-0972 - Internet: www.alutech.com